



ASTRALPOOL 



THE BEST PERFORMING ASTRALPOOL PUMPS

RELAX AND ENJOY THE SILENCE OF YOUR POOL



FLUIDRA

www.fluidra.co.th

Victoria Plus Silent Pump

VICTORIA PLUS
SILENT



Silent



User Friendly
Display



Savings



Easy to
Replace



Connect



Reliable



ปั๊มรุ่น Victoria Plus Silent ออกแบบใหม่ เสียงเงียบกว่าเดิมขณะเครื่องทำงาน

A self-priming pump with single-phase and three-phase motors of 0.5 HP to 3 HP. A prefilter is mounted on the body of the pump to prevent foreign bodies from entering it that may damage its hydraulic parts. The motors supplied come with an IP-55 protection rating and have been prepared to withstand hot environments and high levels of humidity.

The main characteristics of Victoria Plus Silent are:

- Low noise level: between 61dBA–70dBA
- Easy to use: Prefilter cap with 2 levers included (no spanner needed)
- Compatibility: Fully compatible in pools fitted with a Victoria Plus pump

CODE	ITEM	SPECIFICATION						CONNECTION	SOUND LEVEL
		POWER			ELECTRICITY		FLOWRATE @ 8m		
		HP	kW Input	kW Output	Volt	Current (A)	m ³ /hr	Inch	
65557	Victoria Plus Silent Pump 0.5 HP 230 V II ปั๊มรุ่น วิคตอเรียพลัส ซีเลนท์ 0.5 แรงม้า 1 เฟส	0.5	0.6	0.45	230	2.6	11	1.5	61dB
65560	Victoria Plus Silent Pump 0.75 HP 230 V II ปั๊มรุ่น วิคตอเรียพลัส ซีเลนท์ 0.75 แรงม้า 1 เฟส	0.75	0.65	0.47	230	2.9	11	1.5	61dB
65562	Victoria Plus Silent Pump 1 HP 230 V II ปั๊มรุ่น วิคตอเรียพลัส ซีเลนท์ 1 แรงม้า 1 เฟส	1	1	0.76	230	4.3	16	2	61dB
65564	Victoria Plus Silent Pump 1.5 HP 230 V II ปั๊มรุ่น วิคตอเรียพลัส ซีเลนท์ 1.5 แรงม้า 1 เฟส	1.5	1.35	1.04	230	5.8	22.5	2	66 dB
65566	Victoria Plus Silent Pump 2 HP 230 V II ปั๊มรุ่น วิคตอเรียพลัส ซีเลนท์ 2 แรงม้า 1 เฟส	2	1.65	1.32	230	7.3	26.5	2	66 dB
65569	Victoria Plus Silent Pump 3 HP 230 V II ปั๊มรุ่น วิคตอเรียพลัส ซีเลนท์ 3 แรงม้า 1 เฟส	3	2.35	1.89	230	10.3	34	สวมท่อ 1.5" fitting 2"	70 dB
65570	Victoria Plus Silent Pump 3 HP 230/400 V III ปั๊มรุ่น วิคตอเรียพลัส ซีเลนท์ 3 แรงม้า 3 เฟส	3	2.35	1.89	230/400	4.2	34	สวมท่อ 1.5" fitting 2"	60 dB

Alaska Plus Pump



ปั๊มรุ่นอลาสก้าพลัส ใหม่ เจียบกว่าเดิม
ออกแบบใบพัดใหม่ มอเตอร์มาตรฐานเยอรมัน

The Alaska Plus pump new hydraulic design moves water more efficiently and more quietly than any other pumps of its category. Alaska Plus is built to be quiet, durable and reliable. Motor materials are rustproof, stainless steel motor shaft and sealed bearings that never need lubrication. Its thermoplastic housing withstands extreme heat and resist corrosion. Available from 0.5 HP up to 3 HP in both single phase and three phase motors.

- It saves money, as it moves the same required water but with less consumption than our previous pumps.
- The new hydraulic design assures extremely low noise level performance while works at typical conditions.
- A pre-filter with a big strainer has been integrated into the body of the pump to prevent the entry of any foreign bodies which could cause damage to the hydraulic parts of the pump.
- Big strainer basket extends time between cleanings.

CODE	ITEM	SPECIFICATION						CONNECTION
		POWER			ELECTRICITY		FLOWRATE @ 8m	
		HP	kW Input	kW Output	Volt	Current (A)	m ³ /hr	Inch
51858	Alaska Plus Pump 0.5 HP 230 V II ปั๊ม Alaska รุ่น 0.5 แรงม้า 1 เฟส	0.5	0.71	0.46	230	3.0	10	1.5
51860	Alaska Plus Pump 0.75 HP 230 V II ปั๊ม Alaska รุ่น 0.75 แรงม้า 1 เฟส	0.75	0.86	0.64	230	3.7	13	1.5
51862	Alaska Plus Pump 1 HP 230 V II ปั๊ม Alaska รุ่น 1 แรงม้า 1 เฟส	1	1.06	0.88	230	5.1	18	1.5
51864	Alaska Plus Pump 1.5 HP 230 V II ปั๊ม Alaska รุ่น 1.5 แรงม้า 1 เฟส	1.5	1.46	1.15	230	6.8	23	2
51866	Alaska Plus Pump 2 HP 230 V II ปั๊ม Alaska รุ่น 2 แรงม้า 1 เฟส	2	1.85	1.57	230	8.1	29	2
51868	Alaska Plus Pump 3 HP 230 V II ปั๊ม Alaska รุ่น 3 แรงม้า 1 เฟส	3	2.70	1.97	230	11.5	36	2
51869	Alaska Plus 3 HP 230/400 V III ปั๊ม Alaska รุ่น 3 แรงม้า 3 เฟส	3	2.40	2.10	230/ 400	4.5	36	2

Viron Variable Speed Pump



ปั๊มรุ่น Viron สามารถปรับความเร็วได้ 3 ระดับ (high, medium, and low)

Variable speed pumps are born as a new concept of pool pump.

Viron Variable Speed Pumps are the most efficient solution for the pool and their performance can be adapted according to the installation and users' needs.

By increasing and decreasing their speed, not only modify the speed and flow-rate, but also energy consumption. Halving the speed of the pump is able to reduce energy consumption in more than 85%.

In addition, Viron Variable Speed Pumps are controlled through an LCD display with backlighting showing RPM and have 4 timer settings for each day, allowing different speed settings.

CODE	ITEM	SPECIFICATION						CONNECTION
		POWER			ELECTRICITY		FLOWRATE @ 8m	
		HP	kW Input	kW Output	Volt	Current (A)	m ³ /hr	
56550	P320 Viron variable speed pump 1 HP P320 ปั๊ม Viron ปรับระดับความเร็วได้ 1 แรงม้า	1	1.05	0.75	230	7.70	19.2	1.5 - 2
56552	P600 Viron variable speed pump 2 HP P600 ปั๊ม Viron ปรับระดับความเร็วได้ 2 แรงม้า	2	1.89	1.49	230	6.59	32.4	2 - 2.5

CTX High Performance Pump

ปั๊มรุ่น CTX เหมาะกับทั้งสระบ้านและสระขนาดกลาง ที่ต้องการความเงียบในการทำงาน



The AstralPool CTX pump has been designed to comfortably meet the needs and pressures required by your swimming pool and spa equipment. Made from high quality materials and components the CTX is designed to produce greater efficiency and reduce noise levels. Suitable for in-floor cleaning systems, spa jets and other demanding applications. The CTX will provide a high performance and reliability.

CODE	ITEM	SPECIFICATION						CONNECTION
		POWER			ELECTRICITY		FLOWRATE @ 8m	
		HP	kW Input	kW Output	Volt	Current (A)	m ³ /hr	
44453	CTX 280 Pump 1 HP ปั๊ม CTX 280 รุ่น 1 แรงม้า	1	1.07	0.75	230	4.50	16.8	1.5 - 2
44455	CTX 400 Pump 1.5 HP ปั๊ม CTX 400 รุ่น 1.5 แรงม้า	1.5	1.65	1.12	230	7.20	24	1.5 - 2
44456	CTX 500 Pump 2 HP ปั๊ม CTX 500 รุ่น 2 แรงม้า	2	1.90	1.49	230	8.30	30	1.5 - 2

BX High Performance Pump

ปั๊มรุ่น BX เหมาะกับทั้งสระบ้านและสระขนาดใหญ่ สามารถทำงานขณะไม่มีน้ำได้ถึง 24 ชม.



The AstralPool BX pump has been designed to comfortably meet the demands of all your pool equipment while setting new standards of efficiency, convenience and greatly reducing noise levels. With the ability to move more water, use less power in fewer hours per day while requiring less maintenance. The BX pump has to be your next choice.

CODE	ITEM	SPECIFICATION						CONNECTION
		POWER			ELECTRICITY		FLOWRATE @ 8m	
		HP	kW Input	kW Output	Volt	Current (A)	m ³ /hr	
43918	BX Pump 1.5 HP V II ปั๊ม BX รุ่น 1.5 แรงม้า 1 เฟส	1.5	1.65	1.12	230	7.2	26.4	2 - 2.5
43919	BX Pump 2 HP V II ปั๊ม BX รุ่น 2 แรงม้า 1 เฟส	2	2.03	1.49	230	8.8	32.4	2 - 2.5

CODE	ITEM	SPECIFICATION						CONNECTION
		POWER			ELECTRICITY		FLOWRATE @ 8m	
		HP	kW Input	kW Output	Volt	Current (A)	m ³ /hr	
43920	BX Pump 3 HP V II ปั๊ม BX รุ่น 3 แรงม้า 1 เฟส	3	2.30	2.24	230	12.5	38.4	2 - 2.5
43924	BX Pump 3 HP V III ปั๊ม BX รุ่น 3 แรงม้า 3 เฟส	3	2.65	2.24	230/400	4.1	38.4	2 - 2.5

Maxim Pump

ปั๊มรุ่นแมกซิม 3.5 - 5.5 แรงม้า

- Motor has IP-55 protection rating
- Prefilter basket with a capacity of 8 litres • Transparent prefilter lid
- Pump body and supports in plastic, AISI-316 stainless steel motor shaft with double insulation



CODE	ITEM	SPECIFICATION						CONNECTION
		POWER			ELECTRICITY		FLOWRATE @ 8m	
		HP	kW Input	kW Output	Volt	Current (A)	m ³ /hr	
08003	Maxim Pump 3.5 HP V III ปั๊ม Maxim รุ่น 3.5 แรงม้า 3 เฟส	3.5	3.22	2.6	230/400	5.8	56	3
08004	Maxim Pump 4.5 HP V III ปั๊ม Maxim รุ่น 4.5 แรงม้า 3 เฟส	4.5	4.06	3.3	230/400	7.4	74	3
08005	Maxim Pump 5.5 HP V III ปั๊ม Maxim รุ่น 5.5 แรงม้า 3 เฟส	5.5	4.83	4.0	230/400	8.4	88	3

Colorado Pump

ปั๊มรุ่นโคโลราโด แรงใหญ่ เหมาะกับสระเชิงพาณิชย์หรือสวนน้ำขนาดใหญ่

- Bronze impeller, the shaft and prefilter basket in stainless steel
- Plastic centrifugal 3000 r.p.m. pumps with prefilter for swimming pools
- The pump and the prefilter are made of polypropylene reinforced with fibreglass
- Ideal for large volumes at low pressure • Prefilter with a transparent lid for easy accessibility
- Motor protection IP-55 of 3000 r.p.m. at 230/400 V or 400/690 V and 50 Hz from 7.5 HP to 12.5 HP



CODE	ITEM	SPECIFICATION						CONNECTION
		POWER			ELECTRICITY		FLOWRATE @ 8m	
		HP	kW Input	kW Output	Volt	Current (A)	m ³ /hr	
44708	Colorado Pump 7.5 HP ปั๊ม Colorado รุ่น 7.5 แรงม้า	7.5	6.90	5.5	230/400	13.3	130	4
44710	Colorado Pump 10 HP ปั๊ม Colorado รุ่น 10 แรงม้า	10	9.25	7.4	230/400	17.6	145	4
44712	Colorado Pump 12.5 HP ปั๊ม Colorado รุ่น 12.5 แรงม้า	12.5	11.25	9.2	230/400	23.3	160	4

KIVU Pump

ปั๊มพลาสติกกรุ่น KIVU สำหรับสระขนาดใหญ่ เหมาะกับสระเชิงพาณิชย์ หรือ สวนน้ำขนาดใหญ่ : ทุกส่วนที่สัมผัสน้ำเป็นพลาสติก

High efficiency plastic centrifugal pump for commercial pools working at 1.500 r.p.m.

- 3 power modes: 7 HP - 10 HP - 15 HP
- Hydraulic efficiency without prefilter 85% (9906 ISO standard)
- IEC high efficiency motors (IEC 3)
- GS marked
- Low noise level: 66 dBA
- High quality mechanical seal for salt water
- Standard motor shaft (compatible with any pump manufacturer)
- Pump comes with prefilter (in 2 packages: pump + prefilter)



CODE	ITEM	SPECIFICATION						CONNECTION
		POWER			ELECTRICITY		FLOWRATE @ 8m	
		HP	kW Input	kW Output	Volt	Current (A)	m ³ /hr	
56634	KIVU Pump 7.5 HP ปั้ม KIVU รุ่น 7.5 แรงม้า	7.5	7.5	5.6	400/ 690	19.33/ 11.2	160	6 - 5
56637	KIVU Pump 10 HP ปั้ม KIVU รุ่น 10 แรงม้า	10	10	7.46	400/ 690	25.77/ 15	200	6 - 5
56639	KIVU Pump 15 HP ปั้ม KIVU รุ่น 15 แรงม้า	15	14	11.19	400/ 690	36.1/ 21	270	6 - 5

Counter-Current Swimming Kit

ชุดเครื่องว่ายทวนน้ำ

Marlin: inexpensive countercurrent swimming unit. The innovative design and concept supplied as a kit (including faceplate, housing, control box and pump) makes it a feature that will add significant value to your pool. A highly competitive product thanks to its high performance hydraulic features, the Marlin countercurrent system is available in 3 models: the Marlin 30 II, the Marlin 30 III and the Marlin 45 III. Grab rails and hydromassage hose may be added as optional features.



CODE	ITEM	SPECIFICATION						CONNECTION
		POWER			ELECTRICITY		FLOWRATE @ 8m	
		HP	kW Input	kW Output	Volt	Current (A)	m ³ /hr	
45618	MARLIN XS : only faceplate and housing ชุดหน้ากากและเบ้าสำหรับ เครื่องว่ายทวนน้ำ MARLIN	-	-	-	-	-	-	-
35375	MARLIN 3 HP (Single-phase) Nozzle faceplate, housing, control box, pump ชุดสำเร็จเครื่องว่ายทวนน้ำ ป้อนขนาด 3.0 แรงม้า ใช้ไฟ 220 V.	3 HP II	2.9	2.2	230	14	48	D.63
35376	MARLIN 3 HP (Three-phase) Nozzle faceplate, housing, control box, pump ชุดสำเร็จเครื่องว่ายทวนน้ำ ป้อนขนาด 3.0 แรงม้า ใช้ไฟ 230/400 V.	3 HP III	2.9	2.2	230/ 400	7.5	48	D.63
35377	MARLIN 4.5 HP (Three-phase) Nozzle faceplate, housing, control box, pump ชุดสำเร็จเครื่องว่ายทวนน้ำ ป้อนขนาด 4.5 แรงม้า ใช้ไฟ 230/400 V.	4.5 HP III	4.4	3.36	230/ 400	11.34	72	D.63